

Inmarsat IsatPhone 2.1



Brand: Inmarsat
Product Code: 11-400-002
Availability: 1

Price: Fr. 1249.00

Ex Tax: Fr. 1155.41

Short Description

Inmarsat IsatPhone 2.1 is a tough phone for a tough world.

Description

Inmarsat IsatPhone 2.1 is a tough phone for a tough world. The robust handset has been designed to work in any condition, from searing heat to icy blasts; desert sandstorms or monsoon rain.

With fast network registration, an unrivalled battery life offering 8 hours of talk time and up to 160 hours of standby time, you know you can always depend on the **IsatPhone 2**.

The main features of this exciting new handset are:

- Satellite Telephony
- Text and email messaging (text to text, text to email, web message to IsatPhone)
- Longest battery life in industry (talk time 8 hours, standby time upto 160 hours)
- GPS location data – view position and text
- Tracking Button
- Bluetooth for hands-free use
- Incoming call alerts with antenna stowed
- Assistance button (dedicated for emergency)

- IK04 & IP65
- Transflective display with Gorilla glass

IsatPhone 2 gives you the excellent voice clarity and call stability you have come to expect from Inmarsat's network.

In the box

- Quick start guide
- Battery pack
- USB memory stick with user manual
- IsatPhone 2 satellite phone
- Mains charger and 4 universal plug adapters
- Car charger
- Micro USB cable
- Wired hands-free headset
- Wrist strap
- Holster

Specifications

| Communication specs | |
|-------------------------------|---------------------------------------|
| Antenna type | Directional antenna, tiltable |
| Coverage | global without polar areas |
| Data transmission | 2400 bit/s (compressed 9600 bit/s) |
| Frequency range | 1626.5 - 1660.5 / 1525.0 - 1559.0 MHz |
| Provider | Inmarsat |
| Stand by time max. | 160 h |
| Talking time max. | 8 h |
| Construction / technical data | |
| Data connection | Mini-USB |
| DC power voltage | 10-30 V= |
| Dimensions LxWxD | 169 x 75 x 36 mm |
| Display type | LCD w. Gorilla glass |
| Main power voltage | 110-240 V~ |
| Weight | 320 g |
| Environmental conditions | |
| Charging temperatures | 0 °C to +45 °C |
| Leak tightness | IP65 |
| Max. absolute altitude | no information |
| Technical standards | IK04 |
| Temperature range | -20 °C to +55 °C |

