

# Inmarsat IsatPhone 2.1



**Brand:** Inmarsat  
**Product Code:** 11-400-002  
**Availability:** 1

**Price: Fr. 1249.00**

**Ex Tax: Fr. 1155.41**

## Short Description

**Inmarsat IsatPhone 2.1** is a tough phone for a tough world.

## Description

**Inmarsat IsatPhone 2.1** is a tough phone for a tough world. The robust handset has been designed to work in any condition, from searing heat to icy blasts; desert sandstorms or monsoon rain.

With fast network registration, an unrivalled battery life offering 8 hours of talk time and up to 160 hours of standby time, you know you can always depend on the **IsatPhone 2**.

## The main features of this exciting new handset are:

- Satellite Telephony
- Text and email messaging (text to text, text to email, web message to IsatPhone)
- Longest battery life in industry (talk time 8 hours, standby time upto 160 hours)
- GPS location data – view position and text
- Tracking Button
- Bluetooth for hands-free use
- Incoming call alerts with antenna stowed
- Assistance button (dedicated for emergency)

- IK04 & IP65
- Transflective display with Gorilla glass

**IsatPhone 2** gives you the excellent voice clarity and call stability you have come to expect from Inmarsat's network.

### In the box

- Quick start guide
- Battery pack
- USB memory stick with user manual
- IsatPhone 2 satellite phone
- Mains charger and 4 universal plug adapters
- Car charger
- Micro USB cable
- Wired hands-free headset
- Wrist strap
- Holster

### Specifications

Communication specs	
Antenna type	Directional antenna, tiltable
Coverage	global without polar areas
Data transmission	2400 bit/s (compressed 9600 bit/s)
Frequency range	1626.5 - 1660.5 / 1525.0 - 1559.0 MHz
Provider	Inmarsat
Stand by time max.	160 h
Talking time max.	8 h
Construction / technical data	
Data connection	Mini-USB
DC power voltage	10-30 V=
Dimensions LxWxD	169 x 75 x 36 mm
Display type	LCD w. Gorilla glass
Main power voltage	110-240 V~
Weight	320 g
Environmental conditions	
Charging temperatures	0 °C to +45 °C
Leak tightness	IP65
Max. absolute altitude	no information
Technical standards	IK04
Temperature range	-20 °C to +55 °C

