# Iridium Extreme 9575N

**Brand:** IRIDIUM
**Product Code:** 11-103-011
**Availability:** 5

## Price: Fr. 1598.00

**Ex Tax: Fr. 1478.26**

### Short Description

Iridium 9575 is compact, light, and easy to use right out of the box-

### Description

Iridium 9575 is compact, light, and easy to use right out of the box. It’s engineered to withstand rugged environments and connected to the only truly global mobile network — so you can depend on it as a communications lifeline whenever and wherever it’s called for.

### Lieferumfang

- High performance battery 2'300 mAh
- Travel charger for mains operation incl. 5 adapters
- Mobile charger with lighter plug
- Protective cover
- USB data cable
- User Manual (English only)
- Quick Start Guide
- CD-ROM with software
- Accessory adapter (2x)
- Magnetic vehicle antenna with 1.5m cable
- Hand-free set with earphone and microphone

## Specifications

| | |
|---|---|
| Communication specs | |
| Antenna type | Teleskop ausziehbar |
| Coverage | weltweit |
| Data transmission | 2400 bit/s (komprimiert 9600 bit/s |
| Frequency range | 1616.0 - 1626.5 MHz |
| Provider | Iridium |
| Stand by time max. | 30 h |
| Talking time max. | 4 h |
| Construction / technical data | |
| Capacity | 2'300 mAh @ 3.7 V |
| Data connection | Mini-USB |
| DC power voltage | 10-32 V= |
| Dimensions LxWxD | 140 x 60 x 27 mm |
| Display type | LCD |
| Main power voltage | 110-240 V~ |
| Weight | 247 g |
| Environmental conditions | |
| Charging temperatures | 0 °C bis +45 °C |
| Leak tightness | IP65 |
| Max. absolute altitude | 12'192 m.ü.M = 40'000 ft |
| Technical standards | MIL-STD 810F |
| Temperature range | -65 °C bis +71 °C |

## Product Gallery